



VisionPod

Podium screen



Shenzhen iDisplay Technology Co.,Ltd.

Add: 3rd Floor,5th Building, FLT industrial park, Longhua, Shenzhen, China
Factory: 5th Building, No.6 of Xinhua Avenue, Chengjiang, Zhongkai, Huizhou, China
Tel phone: 86-755-85280348
E-mail: hello@idisplayled.com
www.idisplayled.com

Description

GlidePod is a flexible LED display podium delivering stunning HD visuals that enhance presentations with strong visual impact. Its modular design supports customizable sizes to fit various venues and layouts. Built with a sleek black powder-coated steel frame, it combines modern aesthetics with durability, serving as a striking focal point even when standalone. The plug-and-play system enables quick setup, supporting laptop control and full system integration. Multiple input interfaces accommodate diverse content formats. Ideal for corporate meetings, showrooms, product launches, multimedia classrooms, and training spaces, GlidePod ensures professional and effective presentations.



Specifications

Model	P1.2	P1.5	P1.875	P2	P2.5	P3	P4
Application	indoor	indoor	indoor	indoor	indoor	indoor	indoor
Pixel Pitch	1.25mm	1.53mm	1.875mm	2mm	2.5mm	3mm	4mm
Physical Density	640000	422500	284444	250000	160000	111111	62500
LED Type	SMD1010	SMD1212	SMD1515	SMD1515	SMD1515	SMD2121	SMD2121
Module Size	320*160mm	320*160mm	320*160mm	320*160mm	320*160mm	320*160mm	320*160mm
Module Resolution	256*128pixels	208*104pixels	172*86pixels	160*80pixels	128*64pixels	104*52pixels	80*40pixels
Color Temperature	6000K-12000K adjustable						
Viewing Angle (W/H)	140° / 140°						
Brightness	500-600cd/m²	500-600cd/m²	500-600cd/m²	500-600cd/m²	600-700cd/m²	600-700cd/m²	600-700cd/m²
Refresh Rate	3840Hz						
Frame Frequency	60Hz						
Dead pixel Rate	<0.0001						
Life Time	80000 hours						
Supported image formats	DAT、MPG、VOB、TS、AVI、MKV、MP4、MOV、3GP、FLV、NEBM						
Memory	1GB RAM onboard with 16GB storage						
control way	Ethernet, Wi-Fi, USB, 4G optional						
Display size	320*960mm				480*960mm		
Avg/Max power consumption	168/68W				253/100W		
G.W (kg) with flight case	60kg				70kg		
N.W(kg)	22kg				30kg		



Easy Maintenance

with suction tool, front main-
tenance becomes very quick
and easy.



Flight case


Packed in a flight box, it is
impact-resistant, waterproof
and insulating to ensure the
safety of the product during
transportation.



Easy Control

Effortlessly control the display
via computers, mobile phones,
or iPads.

Supports USB, HDMI, Wi-Fi for
local control, and optional 4G
transmission for remote access.



Plug and Play

No need for special installation,
just plug in and use



Application:

Suitable for corporate meetings, showrooms, product launches,
multimedia classrooms, and training spaces.

