TableVision

Immersive Viewing in Every Direction



ISPLAY

Shenzhen iDisplay Technology Co.,Ltd.

Add: 3rd Floor,5th Building, FLT industrial park, Longhua, Shenzhen, China Factory: 5th Building, No.6 of Xinhua Avenue, Chengjiang, Zhongkai, Huizhou, China Tel phone: 86-755-85280348
E-mail: hello@idisplayled.com
www.idisplayled.com

Description

TableVision It is a 3-sided display LED tabletop screen. This table is designed for displaying logos and dynamic videos. It is equipped with advanced electronic functions, allowing you to customize the content according to various occasions. It is perfect for corporate receptions, trade booths, conference events, etc.



Control of the Contro									
Pixel Pitch	1.953	2.6mm	2.97mm	3.91m	4.81m	2.97mm	3.91m	4.81m	5.95m
LED Configuration	SMD1515	SMD1515	SMD2020	SMD2020	SMD2020	SMD1415	SMD1921	SMD1921	SMD3535
Pixel Density	262144dot/m ²	147,456dot/m²	112,896dot/m ²	65,536dot/m ²	43,223dot/m ²	112,896dot/m ²	65,536dot/m²	43,223dot/m²	28224dot/m²
Module size	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm	250*250mm
Module Resolution	128*128	96x96dot	84x84dot	64x64dot	52x52dot	84x84dot	64x64dot	52x52dot	42*42dot
Cabinet Resolution	256x256/512dot	192x192/384dot	168x168/336dot	128x128/256dots	104x104/208dots	168x168/336dot	128x128/256dots	104x104/208dots	84x84/168dots
Cabinet Weight	8kg/12. 5kg					9kg/13.5			
IP Rating	IP23					IP65			
Environmental	Indoor					outdoor			
Brightness	600-700CD/m	700-800CD/m ²	700-800CD/m ²	700-800CD/m ²	700-800CD/m ²	4000-4500CD/m ²	4000-4500CD/m ²	4000-4500CD/m ²	5000-5500CD/m ²
View Distance	>2	>2.6m	>2.9m	>4m	>5m	>2.9m	>4m	>5m	>6m
Viewing Angle	140°/140°								
Max.Power Consumption	450W/m²					800W/m²			
RefreshFrequency	3840Hz								
Box size	500*500mm and 500*1000mm								
Brightness Adjustm ent	0-100 levels adjustable								
Operation Power	AC100~24050/60Hz								
Supported image formats	DAT、MPG、VOB、 TS、AVI、MKV、MP4、MOV、3GP、FLV、NEBM								
Memory	1GB RAM onboard with 16GB storage								
control way	Ethernet, Wi-Fi, USB, 4G optional								
Avg/Max power usage	600w / 2200w								

Remote Control

Support remote control from computers, mobile phones, and iPads. Support USB, HDMI, Wi-Fi and 4G transmission methord
















PC+HDMI/40 Ethernet

Flight case

Packed in a flight box, it is impact-resistant, waterproof and insulating to ensure the safety of the product during transportation.







Silent wheels

High-quality silent wheels, no noise during movement, with positioning and height adjustment functions.

Easy Maintenance

with suction tool, front maintenance becomes very quick and easy.



Plug and Play

No need for special installation, just plug in and use



Usage scenarios

The three-sided display LED desktop screen can display content from multiple angles simultaneously, suitable for company reception desks, exhibitions, conferences, etc.

