


iflex lite

High Flexibility & Highly Customizable

iDISPLAY

Shenzhen iDisplay Technology Co.,Ltd.

Add: 3rd Floor, 5th Building, FLT industrial park, Longhua, Shenzhen, China
Factory: 5th Building, No.6 of Xinhua Avenue, Chengjiang, Zhongkai, Huizhou, China
Tel phone: 86-755-85280348
E-mail: hello@idisplayled.com
www.idisplayled.com



Ultra-thin & Ultra Light

the weight is only 150g with bottom frame and mask and thickness is less than 8mm

Seamless Panel Connection

Modules are stitched together via magnetic connection, this magnetic buckle design also ensures fast installation and replacement.

We support custom design to make oval, sphere, wavy, curved and cylinder shapes at will



	ITEM	P1.25	P1 .5	P1 .6	P1 .8	P2	P2 .5	P2 .6	P3	P4	P5
LED Module	LED	SMD 3 IN 1									
	Pixel Pitch (mm)	1.25	1.5625	1.667	1.8605	2	2.5	2.604	3	4	5
	Module Resolution (WxH)	160x120	128x96	120x90	172x86	128x64	128x64	96x48	80x40	64x32	64x32
	Module Size (WxH)	200x150	200x150	200x150	320x160	256x128	320x160	250x125	240x120	256x128	320x160
	Module Weight (kg/pcs)	0.2-0.3									
	Module Quantity (WxH)	Customized based on project requirements									
Cabinet	Cabinet Resolution	Customized based on project requirements									
	Cabinet Size (WxH mm)	Customized based on project requirements									
	Pixel Density		409,600	360,000	288,906	250,000	160,000	147,456	111,111	62,500	40,000
	Weight (kg/m2)	32									
	Cabinet Material	Iron									
	Ingress Protection	IP30									
Electrical Parameter	Maintenance	Front Service only									
	Color Temperature (K)	3200-12000 (Adjustable)									
	Brightness (nit)	600-800					700-1000				
	View Angle	H 140 ° / V 140 °									
	Contrast Ratio	4000:1									
	Max Power Consumption(W/m2)	600	600	600	600	600	600	600	600	550	550
Usage Environment	Average Power Consumption(W/m2)	200	200	200	200	200	200	200	200	185	185
	Working Voltage(V)	AC110/220V									
	Refresh Rate (HZ)	≥3840									
	Life (H)	50000									
	Working Temperature (°C)	-10°C~-+40°C									
	Storage Temperature (°C)	-20°C~ +60°C									
	Working Humidity(RH)	10~60%									
	Storage Humidity(RH)	10~60%									
	Application	Indoor Only									



Easy Maintenance

with suction tool, front maintenance becomes very quick and easy

