Arcvision

Flexible Rental LED Displays, Unlocking Creativity



ISPLAY


Shenzhen iDisplay Technology Co.,Ltd.

Add: 3rd Floor,5th Building, FLT industrial park, Longhua, Shenzhen, China Factory: 5th Building, No.6 of Xinhua Avenue, Chengjiang, Zhongkai, Huizhou, China Tel phone: 86-755-85280348
E-mail: hello@idisplayled.com

Description

This ultra-flexible display offers unparalleled flexibility, easily shaping into large concave, convex, cylindrical, or 90° curved forms. Perfect for creating stunning and creative stage setups, it's the ultimate choice to unleash endless possibilities!

	Application environment	Indoor			Outdoor	
	Pixel Pitch	2.6mm	2.97mm	3.91mm	2.97mm	3.91mm
	Pixel Dot	96x96	84x84	64x64	84x84	64x64
	LED Driving Method	1/32 scan	1/28 scan	1/16 scan	1/21 scan	1/16 scan
	LED Type	SMD (2121)			SMD(1921)	
	Pixel Configuration	1R1G1B			1R1G1B	
	LED Module Size	Soft board 250*250mm			Soft board 250*250mm	
	Cabinet Size	500*500mm			500*500mm	
	Net Weight/Cabinet	6kg			7.5kg	
	Power	AC220/110±10%, 47~63 Hz			AC220/110±10%,47~63 Hz	
	Serviceability	Rear maintenance			Post-maintenance	
7	Max. Power Consumption	≤600 W/m²			≤600 W/m2	
	Avg. Power Consumption	≤300 W/m²			≤400 W/m2	
ı	Viewing Angle (H/V)	120°/120°			120°/120°	
	Brightness	600cd/m²			4500cd/m2	
	Certifications	CCC, FCC			CCC, FCC	
	Contrast Ratio	3,000:1			3,000:1	
	Operating Temperature	-10°C to +45°C			-20°C to +50°C	
	Operating Humidity	20% to 90%			20% to 90%	
	Lifetime (50% Brightness)	100,000 hours			100,000 hours	
	Processing	14 bit			14 bit	
1	Colors	281 trillion			281 trillion	
	Refresh Rate	≥3840-7680 Hz			≥3840-7680 Hz	
	Frame Rate	60 Hz			60 Hz	
	Waterproof rating	IP31			Front IP65 / Rear IP65	



Cabinet Size: 500x500mm

Unmatched flexibility

The mechanical unit can be freely bent, allowing each box to achieve s-shaped, inward, and outward curved formations.



Advantages

Handle

Stainless steel quick lock

Arc adjuster (Maximum angle 22.5°)

> Metal test button + indicator light

One-handed operation quick lock nut Box corner guard

Module upper and lower locks

Power plug


Quick disassembly power box

Signal plug

Dual backup network ports


Features

- Straight/curved lock with strong strength
- Hanging, floor stacking and wall mounted
- Front and rear serviceable
- Corner Protect to protect led from damage



Flexible Installation options

Supports suspension and stacking, with compact suspension blocks and brackets featuring independent connectors for perfect curved screen installation.



Compact cylindrical design

The Arcvision is ideal for stages with limited space, allowing







Stacking

Case study

